

Bridgestone GeoGrip

Maschinen Gewicht	Produkt Bezeichnung	Platten Breite	Dimensionen in mm				Bohrloch Durchmesser	Abstand der Glieder	Schrauben Drehmoment (kg-m)
			A	B	C	D			
- 3.0 ton	GE250BS	250	110.00	138.00	30.00	38.00	M12	102.00	10 +/- 1.0
4.0 - 6.5 ton	GE400BS	400	80.00	104.00	46.00	45.00	12,50	135.00	16.5 +/-1.5
4.0 - 6.5 ton	GE400CS	400	72.00	99.00	43.40	45.00	13.30	135.00	16.5 +/-1.5
4.0 - 6.5 ton	GE400FS	400	66.00	90.00	46.00	45.00	12,50	135.00	16.5 +/-1.5
6.5 - 10.0 ton	GE450AS	450	73.00	89.00	57.00	54.00	14.50	154.00	25.0 +/- 2.5
6.5 - 10.0 ton	GE450BS	450	90.00	90.00	55.00	54.00	14.50	154.00	25.0 +/- 2.5
6.5 - 10.0 ton	GE450ES	450	83.00	83.00	52.00	54.00	12,50	140.00	25.0 +/- 2.5
10.0 - 15.0 ton	GE500BS	500	107.90	107.90	60.30	73.00	16.50	171.45	42.0 +/- 3.0
15.0 - 30.0 ton	GE600AS	600	124.40	160.40	62.00	91.00	20.50	190.00	32.0 to 47.0
15.0 - 30.0 ton	GE600CS	600	119.60	155.60	69.00	91.00	21,10	190.00	32.0 to 47.0

